















# ТАБЛИЦА РАСХОДА ВОДЫ ФОРСУНКАМИ

Протестировано в лабораторных условиях.  
1 Галлон США = 3.78 Литров  
\*\*\*Данные для других диаметров по запросу

Табл.: расход воды (GPH) (LPH) (LPM) для указанного давления (BAR) (PSI)

ORIFICE DIAMETER	BAR	3	4	7	10	15	25	35	45	70	84	100
	PSI	42	56	100	142	213	355	500	640	1000	1200	1420
 0,15  .006"/.15 mm	GPH		--	--	--	--	0,44	0,52	0,60	<b>0,73</b>	0,80	0,93
	LPH						1,68	1,98	2,28	<b>2,76</b>	3,06	3,54
	LPM						0,0280	0,0330	0,0380	<b>0,0460</b>	0,0510	0,0590
 0,20  .008"/.20mm	GPH		--	--	--	--	0,77	0,92	1,05	<b>1,25</b>	1,55	1,60
	LPH						2,88	3,41	3,86	<b>4,72</b>	5,88	6,06
	LPM						0,0480	0,0568	0,0643	<b>0,0787</b>	0,0980	0,1010
 0,30  .012"/.30mm	GPH	0,37	0,43	0,55	0,68	0,78	1,03	1,23	1,41	<b>1,74</b>	2,52	2,63
	LPH	1,34	1,55	2,05	2,45	3,00	3,87	4,74	5,20	<b>6,48</b>	9,54	9,96
	LPM						0,0645	0,0790	0,0867	<b>0,1080</b>	0,1590	0,1660
 0,40  .015"/.40mm	GPH	0,51	0,59	0,76	0,93	1,07	1,42	1,69	1,93	<b>2,39</b>	3,09	3,19
	LPH	1,81	2,13	2,81	3,36	4,12	5,32	6,29	7,14	<b>8,90</b>	11,70	12,06
	LPM						0,0887	0,1048	0,1190	<b>0,1483</b>	0,1950	0,2010
 0,50  .020"/.50mm	GPH	0,69	0,80	1,03	1,26	1,46	1,93	2,31	2,63	<b>3,26</b>	4,23	4,36
	LPH	2,51	2,90	3,83	4,58	5,61	7,24	8,57	9,72	<b>12,12</b>	16,02	16,50
	LPM						0,1207	0,1428	0,1620	<b>0,2020</b>	0,2670	0,2750
 0,80  .030"/.80mm	GPH									<b>4,43</b>		
	LPH									<b>16,80</b>		
	LPM									<b>0,2800</b>		
 1,00  .040"/1.00 mm	GPH									<b>7,13</b>		
	LPH									<b>27,00</b>		
	LPM									<b>0,4500</b>		

## Рабочая зона стандартной форсунки (размеры указаны для форсунок Ø 0.15 - 0.20)

